

EXCO NEMA 3R MANUAL TRANSFER

SWITCHES: **EX-DTNF-400A-N3R**

FEATURES

400AMP Non-fused NEMA 3R Manual Transfer Switch. The enclosure is NEMA 3R rated for protection against water, moisture, and debris. This rating allows the non-fused to be used in indoor and outdoor areas. Enclosure can be customized to your need and specifications, some examples are:

- Adding single pole camlock connectors for quick connections
- adding heaters for cold environments
- Adding powering meters
- Aiding alarm relays for trip notification down stream

BUILD LIST

CATALOG #	QTY.	DESCRIPTION
*5412 ES362412	1	EL ENCLOSURE 36X24X12 NEMA 3R-WATER, OIL, AND DUST TIGHT ENCLOSURE
OT400U30C	1	3P XFER SW 400A NF D-D RH UL98
OSP12X535	1	PISTOL SHAFT
OHB125J12E011	1	PISTOL HANDLE, I-O-II
OZKA-200	2	LUG KIT, OT/OS 400 LUG KIT 2-600, QTY. 6 PER BAG
TNIA-400	1	INSULATED GROUND NEUTRAL ONLY
TA-2/0	3	1 CONDUCTOR COPPER/ALUMINUM LUG
OTZC23	1	CONNECTION BAR

SPECIFICATIONS

ITEM #	EX-DTNF-400A-N3R	DIMENSIONS (HxWxD) :	36X24X12 INCHES
BRAND	EXCO	POLES	3
MOUNTING	PANEL	NET WEIGHT	113 LBS.
CURRENT RATING	400 AMPS	STANDARDS	UL 98/ IEC60947-3
VOLTAGE	600 V MAX		

STANDARDS:

The EXCO Engineering Department is Available to Assist you in the Selection of Enclosures and Accessories.

UL 98
IEC60947-3

