EXCO NEMA 3R MANUAL TRANSFER

SWITCHES: EX-DTNF-200A-N3R



200AMP Non-fused NEMA 3R Manual Transfer Switch. The enclosure is NEMA 3R rated for protection against water, moisture, and debris. This rating allows the non-fused to be used in indoor and outdoor areas. Enclosure can be customized to your need and specifications, some examples are:

- Adding single pole camlock connectors for quick connections
- adding heaters for cold environments
- Adding powering meters
- Aiding alarm relays for trip notification down stream

| BUILD LIST | | | | |
|--|------------------|---|---------------------|-------------------|
| CATALOG # | QTY. | DESCRIPTION | | |
| SCE-30EL2010LP OT200U30C | 1 1 | EL ENCLOSURE 30x20x10 NEMA 3R-WATER, OIL, AND DUST TIGHT ENCLOSURE 3P XFER SW 200A NF D-D RH UL98 | | |
| OXP10X500 | 1 | PISTOL SHAFT | | |
| OHB125J10B | 1 | PISTOL HANDLE, 19.7 10x500 | | |
| OZKA-200 TNIA-400 TA-2/0 OTZC13 | 2 1 3 1 | LUG KIT, OT/OS 200 LUG KIT 4-300, QTY. 6 PER BAG INSULATED GROUND NEUTRAL ONLY 1 CONDUCTOR COPPER/ALUMINUM LUG CONNECTION BAR, 3P JUMPER BARS | | |
| SPECIFICATIONS | | | | |
| ITEM # | EX-DTNF-200A-N3R | | DIMENSIONS (HxWxD): | 30x20x10 INCHES |
| BRAND | EXCO | | POLES | 3 |
| MOUNTING | PANEL | | NET WEIGHT | 70 LBS. |
| CURRENT RATING | 200 AMPS | | STANDARDS | UL 98/ IEC60947-3 |
| VOLTAGE | 600 V MAX | | | |
| | | | | |

STANDARDS:

The EXCO Engineering Department is Available to Assist you in the Selection of Enclosures and Accessories

UL 98 IEC60947-3





