

GUARDED LED INDICATOR LIGHTS

FEATURES

- Suitable for long & short barrel applications all candelabra base LED lights can be replaced from the front by removal of the lens cap.
- Made with 3/4" NPSM threads.
- All LED indicator lights have 8" flexible leads, other lengths on special order, or screw terminal.
- Add suffix T to P/N for screw terminal
- All lens caps are black anodized aluminum finished with colored glass lens.
- Maximum Installation thick: 1-11/16" on long barrel (long series) and 5/8" on short barrel (short series).



STANDARD SERIES

Long Barrel Cat #	Short Barrel Cat#	Description	Weight (lbs.)
XLRL-GH	XLSRL-GH	Red	1/2
XLAL-GH	XLSAL-GH	Amber	1/2
XLGL-GH	XLSGL-GH	Green	1/2
XLWL-GH	XLSWL-GH	White	1/2
XLBL-GH	XLSBL-GH	Blue	1/2

120V dual polarity supplied as standard.
12 or 24 volts optional, consult factory.

LED Advantages:

- 10 year/100,000 hour service life under normal ambient conditions.
- Up to 4x more energy efficient
- Improved resistance to shock & vibration.
- LED's operate significantly cooler than traditional lamps.
- Ultra bright cluster LED's.

CERTIFICATIONS:

The EXCO Engineering Department is Available to Assist you in the Selection of Enclosures and Accessories.

Class I, Division I, Groups B, C, & D
Class II, Groups E, F & G
NEMA 3,4 ,7, & 9/IP66



EMAIL: TEAMEXCOINDUSTRIAL@GMAIL.COM

