XHP: EXPLOSIONPROOF/ FLAMEPROOF PUSHBUTTONS

FEATURES

- Durable die-cast aluminum barrels
- Exposed aluminum components are anodized for superior corrosion and UV resistance
- Heavy-duty nylon buttons
- Long-lasting anodized aluminum heads (mushroom heads only)
- Designed for installation into 3/4" NPSM entries

PUSHBUTTONS & ACCESSORIES		
CATALOG #	DESCRIPTION	WEIGHT (lbs.)
XHPB*	Long Barrel Momentary Pushbutton	1/2
XHPBS*	Short Barrel Momentary Pushbutton	1/2
XHPBPL*	Long Barrel Momentary Pushbutton w/Pad-lock Provision (holds button in depressed position)	1/2
XHPBSPL*	Short Barrel Momentary Pushbutton w/Pad-lock Provision (ho;ds button in depressed position)	1/2
ХНРВМ	Long Barrel Red Momemtary Mushroom Head Pushbutton	1/2
XHPBMS	Short Barrel Red Momemtary Mushroom Head Pushbutton	1/2
XHPPM	Long Barrel Maintained Mushroom Head Pushbutton (includes 1NO/1 NC contact block)	1/2
XHPPMS	Short Barrel Maintained Mushroom Head Pushbutton (includes 1NO/1 NC contact block)	1/2
7716	Guard for Mushroom Head Pushbutton	1/4
XBB	Silicone Rubber Protective Boot for XHPB/XHPBS- Black	1/4
XBG	Silicone Rubber Protective Boot for XHPB/XHPBS- Green	1/4
XBR	Silicone Rubber Protective Boot for XHPB/XHPBS- Red	1/4
XHPL	Silicone Rubber Protective Boot for XHPB/XHPBS- Black	1/4
XHPL	Pad-Lock Cover for XHPB/XHPBS (holds button in depressed position)	1/4
XHPLG	Pad-Lock Cover for XHPB/XHPBS (protects button from unauthorized actuation)	1/4

^{*}Standard pushbutton color is black. Red and Green are available. Please specify when ordering.

(MATERIAL)

- Barrels are 6061-T6 aluminum
- Caps are anodized 6061-T6 aluminum
- Buttons are nylon
- Mushroom head buttons are anodized 6061-T6 aluminum

DESIGN OPTIONS

- Short and long-barrel (for enclosure covers thicker than 3/4")
- Variety of colors to choose from
- Pad-lock provision (sold separately)
- Guards avaliable
- Various contact block configurations (sold separately)
- Installed in Adalet/Exco Enclosures with no installation charge
- Mushroom head buttons available as monentary or maintained
- Protective boots available for N4X requirements







(Shown on XPBM)

CERTIFICATIONS

The EXCO Engineering Department is Available to Assist you in the Selection of Enclosures and Accessories.

Class 1, Division 1 & 2, Groups B, C, & D Class 2, Division 1 & 2, Groups E, F, & G

Class 3, NEMA Type 4, 7, & 9

NEMA Type 4X (with stainless steel cover bolt option)

UL1203/CSA C22.2 NO. 25 & 30 UL1203/CSA C22.2 NO. 25 & 30 UL1203/CSA C22.2 NO. 25 & 30 UL50

For extremely wet-dirty location applications, XHPB and XHPBS series are available to be used with protective boots.