

**XLP:****EXPLOSIONPROOF/ FLAMEPROOF ILLUMINATED PUSHBUTTONS****FEATURES**

- Durable die-cast aluminum barrels
- Exposed aluminum components are anodized for superior corrosion and UV resistance
- Guarded lens for protection against impact
- designed for installation into 3/4" NPSM entries
- Standard 120V slide-base lamp

**LONG BARREL**

LED CATALOG #	Incandescent CATALOG #	ATEX-LED Catalog#	Description	Ship Weight (lbs.)
<b>XLPA-G</b>	<b>XLPA-G</b>	<b>XLPA-X-G</b>	Guarded with Amber Lens	0.5
<b>XLPL-G</b>	<b>XLPL-G</b>	<b>XLPL-X-G</b>	Guarded with Blue Lens	0.5
<b>XLPC-G</b>	<b>XLPC-G</b>	<b>XLPC-X-G</b>	Guarded with Clear Lens	0.5
<b>XLPG-G</b>	<b>XLPG-G</b>	<b>XLPG-X-G</b>	Guarded with Green Lens	0.5
<b>XLPR-G</b>	<b>XLPR-G</b>	<b>XLPR-X-G</b>	Guarded with Red Lens	0.5
<b>XLPW-G</b>	<b>XLPW-G</b>	<b>XLPW-X-G</b>	Guarded with White Lens	0.5

**SHORT BARREL**


LED CATALOG #	Incandescent CATALOG #	ATEX-LED Catalog#	Description	Ship Weight (lbs.)
<b>XLPA-S-G</b>	<b>XLPA-S-G</b>	<b>XLPA-S-X-G</b>	Guarded with Amber Lens	0.5
<b>XLPL-S-G</b>	<b>XLPL-S-G</b>	<b>XLPL-S-X-G</b>	Guarded with Blue Lens	0.5
<b>XLPC-S-G</b>	<b>XLPC-S-G</b>	<b>XLPC-S-X-G</b>	Guarded with Clear Lens	0.5
<b>XLPG-S-G</b>	<b>XLPG-S-G</b>	<b>XLPG-S-X-G</b>	Guarded with Green Lens	0.5
<b>XLPR-S-G</b>	<b>XLPR-S-G</b>	<b>XLPR-S-X-G</b>	Guarded with Red Lens	0.5
<b>XLPW-S-G</b>	<b>XLPW-S-G</b>	<b>XLPW-S-X-G</b>	Guarded with White Lens	0.5

**DESIGN OPTIONS**

- Short & long-barrel (for enclosure covers thicker than 3/4")
- Variety of colors to choose from
- LED or incandescent bulbs-12V, 24V, & 120V options
- Various contact block configurations (sold separately)
- Installed in Adalet/EXCO enclosures with no installation charge
- Protective boots available for N4X requirements

**MATERIAL**

- Barrels are 6061-T6 aluminum
- Buttons are nylon
- Mushroom head buttons are anodized 6061-T6 aluminum
- Lenses are tempered glass

**Certifications:**

*The EXCO Engineering Department is Available to Assist you in the Selection of Enclosures and Accessories.*

Class I, Divisions 1 and 2, Groups B, C, and D  
 Class II, Divisions 1 and 2, Groups E, F, and G  
 Class III  
 NEMA Type 4, 7, and 9 / IP66  
 NEMA Type 4X (with stainless steel cover bolt option)

UL1203/CSA C22.2 No. 25 & 30  
 UL1203/CSA C22.2 No. 25 & 30  
 UL1203/CSA C22.2 No. 25 & 30  
 UL50

