



Catalog Number:
UPC Number:

XT4NQ3250BFF000XXX
8886144729

Tmax XT Molded Circuit Breaker, Frame Size XT4 - to 250A, 600V (UL) / 250A, 690V (IEC) ,
Trip Type Thermal magnetic adjustable (TMD/TMA), 3 Poles

North American Specifications (UNSPSC)

UNSPSC	39121616 Molded case circuit breakers
IGCC	4927 Molded case circuit breakers
Brand Name	ABB
Sub Brand	Tmax XT
Type	Molded case circuit breaker
Special Features	Feature high specific let-through current peak and energy limiting characteristics that allow the circuits and equipment on the load side to be sized in Optimum way.
Application	Ideal solution for all distribution levels from the main low voltage switchboard to the sub-switchboards in the installation
Standard	UL 100% rated / IEC dual rated
Frame	XT4 - to 250A, 600V (UL) / 250A, 690V (IEC) -
SCCR	25, 35,65,100, 150, AND 200 kA
Trip Type	Thermal magnetic and Electronic protection
Number Of Poles	Thermal magnetic adjustable (TMD/TMA) 3 Poles

Packaging

Outer Quantity	1
Outer Dimensions (inches)	6.614x5.709x8.268
Weight Uom	5.36 lbs. Each